

## L@titude Network Vision Annunciator

LRC00NC-10 (Red), LRC00NC-40 (Gray), and LRC00NC-60 (Black)



## **Product Overview**

The L@titude Network Vision Annunciator is the most qualified annunciator on the market. It is a full-color graphical display and touchscreen. It represents the most versatile annunciator for life safety systems available today. The Annunciator is a full-function fire alarm repeater that is configurable and application-flexible for use in applications such as hospital nursing stations and elevator alarms.

L@titude Network Vision Annunciators can be configured to fully replicate fire control panel functionality, or to operate as simple, display-only devices for applications where access to fire alarm controls are inappropriate.

## Standard Features

- Full color 7" (800 x 480 pixel) interface
- Replicates information displayed at the FACP
- Automatic display brightness adjustment
- Internal buzzer
- Connects via control panel network terminals
- · Low current, 24V DC powered
- Configurable functionality
- Enable key-switch
- Sheet steel enclosure
- Surface or semi-flush enclosure options available

Technical Specifications	
Supply Voltage Range	21-30V DC
Quiescent Current during Power Failure	232mA - Buzzer off, touch panel back-light on 164mA - Buzzer off, touch panel back-light off 268mA - Buzzer on, touch panel back-light on 195ma - Buzzer on, touch panel back-light off
Maximum Number of Units on a Network	31 Annunciators
Size	9.25" x 6.7" x 2.2" (235 mm x 170 mm x 55 mm)
Display	Full color 800 x 480 LCD with resistive touch screen and automatic back-light dimming
Construction	18 SWG, 1.2 mm mild sheet steel
Cable Entry	2 x 20 mm knockouts on top & bottom 3 x 20 mm and 2 x 28 mm knockouts in back
Vision Annunciator Electronics Only	S787
Finish	Epoxy powder coated
Color	Red (RAL3002) Gray (BS 00 A 05) Black (RAL9005)
Optional Semi-Flush Mounting Collar Kit	KM1098RD - Red KM1098GY - Gray KM1098BS - Black
Weight	4.4 lbs (2 kg) maximum
IP Rating	IP30